

Kondo

KONDO is a ceramic tile series inspired by the past, based on the elegance of old ceramic tiles and the originality of hydraulic tiles. Its only purpose is to surprise and fall in love, through its oxide finishes that reflect the wear of the metal.

This series allows obtain numerous decorative alternatives for its multiple combinations of designs, colors and metallic finishes, to be able to adapt to the needs of each design proposal.

KONDO es una serie cerámica inspirada en el pasado, basada en la elegancia de las antiguas baldosas y en la originalidad de los azulejos hidráulicos. Su único propósito es sorprender y enamorar, a través de sus acabados en óxido que reflejan el desgaste del metal.

Esta serie permite obtener numerosas alternativas decorativas gracias a sus múltiples combinaciones de diseños, colores y acabados metalizados, para poder adaptarse a las necesidades de cada propuesta de diseño.





Kondo

White body / *Pasta blanca*
Thickness: 7mm (0,26") / *Espesor: 7mm*
Not rectified / *No rectificado*



15x15 cm
6"x6"

Matt Finish / *Acabado Mate*
Wallcovering use / *Revestimiento de paredes*
Indoor / *Interior*

Cream



Forest



Smoke



Cream Silver

Cream Gold



Forest Silver

Forest Gold

Smoke Silver

Smoke Gold






Kondo 1



Kondo 2



Kondo 3



Technical Data

Laying advice

1. Choosing a ceramic tile

When choosing a ceramic tile to cover a certain surface, attention must be paid to a series of aesthetical (color, design, texture, etc.) and technical (physical-chemical features, etc.) conditions. The technical factors for an adequate choice will depend on the specific situation, weather conditions in region, and expected use.

The ceramic pieces contained in this catalog are decorated with a thin metal application. Manipulate with special care. Improper handling (scratching and/or scraping) and improper use of abrasive detergents can damage the pieces. Treat these in particular with extreme careful.

These products are not suitable for wet areas like public spas or swimming pools where aggressive saline and/or disinfectant products like bleach are used.

2. Initial verification

Prior to placing the ceramic tile, the client should check that it is in agreement with the requested features (model, quality, shape, tone, gage, etc.). If any ceramic piece is defective, do not use and communicate this to your provider. Not accept any claims once placed the product.

3. Lay out

It is recommended that the layout of the product is prepared before the final installation. The surface for placing the tiles must be flat, firm, stable, compatible with the binding material, and clean.

We recommend using cement glue with polymeric additives as fitting material.

Recommended product: **H40 (Kerakoll)**

Before preparing the binding material, check the manufacturer's indications (way to use, etc).

The bonding materials are applied with a notched trowel to ensure optimal distribution across the surface. Should be avoided that the residues of fitting material get dry, remaining adhered on the surface of pieces, using a slightly damp sponge to clean the tile joints, passing it diagonally across them. Do not use dirty or brackish water.

4. Jointing

For technical reasons, it is not advisable to lay ceramic tiles without the corresponding layout joint.

For choosing the jointing material, one should take into account the place where the tiles (floor or wall) are fitted and their situation (indoor or outdoor), the use of joints with polymeric additives or synthetic resins being recommendable, and not Portland cement grout.

Recommended product: **Fugalite / Fugabella (Kerakoll)**

5. Cleaning









Do not use commercial products known as cement removers or scale removers, acid solutions used mainly to remove cement debris (work debris).

For cleaning excess installation materials before they have dried, use a sponge and plenty of water.

For subsequent cleanings we recommend the use of a soap damp-ened in water and neutral soap. Do not use powder detergents, nor metallic mops or abrasives. Do not use abrasive, acidic or alkaline cleaning products. Use a soft sponge with liquid soap and water to clean the tiles, and then dry them with a fine cloth.

Recommended product: **Fuga Soap (Kerakoll)**

Uses complete list

SERIE	Indoors 	Outdoors 	Wall 	Floor light traffic 	Floor medium traffic 	Shower wall 	Shower floor 	High vapour condensation areas (sauna, turkish bath) 
Abstra	✓	✓	✓			✓		✓
Rake	✓	✓	✓			✓		✓
House	✓	✓	✓			✓		✓
Framed	✓	✓	✓			✓		✓
Mist	✓	✓	✓			✓		✓
2Lines	✓	✓	✓			✓		✓
Slate	✓	✓	✓	✓		✓	✓	✓
Urban	✓	✓	✓	✓		✓	✓	✓
Artic	✓	✓	✓	✓		✓	✓	
Fusion	✓	✓	✓		✓	✓	✓	✓
Tempo	✓	✓	✓		✓	✓	✓	✓
Jurgen	✓	✓	✓			✓		✓
Metrik	✓		✓			✓		✓
Kondo	✓		✓			✓		✓
Trames	✓		✓			✓		✓
2Moreone	✓		✓			✓		✓
Cottage	✓		✓			✓		✓
Become	✓		✓			✓		✓
2Geom	✓		✓			✓		✓
Cosmos	✓		✓			✓		✓